

**FLYTECH**

# K730N SERIES

New Ultra-Slim Panel PC



## KEY FEATURES

- Integrated with Intel® Elkhart Lake and Tiger Lake processors
- Compatibility with Windows 10, Linux, and Android 13
- Available in 15.6", 18.5", and 21.5" widescreen options
- Seamless peripheral integration into any workspace layout
- Swiftly access and replace SSD by simply removing the rear plate
- Transformable mounting solutions for a versatile setup
- Built-in universal VESA mounts (75mm and 100mm)



**POS Stand**



**Printer Stand**



**Floor Stand**

## SCREEN SIZES



## MODULARIZED 4-SIDED PERIPHERAL



## SPECIFICATIONS

	Motherboard	F35	F85U
<b>System</b>	Processor	Intel®Elkhart Lake Celeron J6412	Intel®Tiger Lake i3-1115G4E
	Memory	4GB DDR4	4GB DDR4
	Storage	128GB SSD (M.2)	128GB SSD (M.2)
<b>Display</b>	Size and Resolution	K737N: 15.6" 1920 x 1080 K738N: 18.5" 1366 x 768 K739N: 21.5" 1920 x 1080	K737N: 15.6" 1920 x 1080 K738N: 18.5" 1366 x 768 K739N: 21.5" 1920 x 1080
	Touch Screen	True-Flat PCAP multi-touch	True-Flat PCAP multi-touch
<b>I/O Ports</b>	USB Type-A	2 x USB3.0, 4 x USB2.0	4 x USB3.0, 2 x USB2.0
	USB Type-C	1 x USB3.0 full-functioned (DP/ PD 5V/3A, 12V/3A)	1 x USB3.0 full-functioned (DP/ PD 5V/3A, 12V/3A)
	FeDP	1 x Flytech proprietary miniDP (for 2nd display)	1 x Flytech proprietary miniDP (for 2nd display)
	Serial Port	3 x RJ48	3 x RJ48
	LAN	1 x RJ45	1 x RJ45
	Cash Drawer	1 x RJ11	1 x RJ11
	DC Jack	1x 4PIN (with latch)	1x 4PIN (with latch)
<b>Optional I/O</b>	Powered USB	2x Powered USB 12V 1x Powered USB 24V	2x Powered USB 12V 1x Powered USB 24V
<b>Audio</b>	Internal Speaker	1 x 3W	1 x 3W
<b>Indicator</b>	Power Button w/ LED	1	1
<b>Power</b>	Power Adapter	65W / 19V (120W/19V with PUSB12V & 24V)	120W / 19V
<b>Communication</b>	WLAN + BT	802.11 series + BT5.1 (Option)	802.11 series + BT5.1 (Option)
<b>Peripheral (option)</b>	Camera	5MP Camera w/ microphone (USB)	5MP Camera w/ microphone (USB)
	MSR	3-Track MSR (USB)	3-Track MSR (USB)
	Fingerprint	Fingerprint Reader (USB)	Fingerprint Reader (USB)
	NFC	NFC Reader (USB)	NFC Reader (USB)
	Scanner	2D Scanner (USB)	2D Scanner (USB)
	Light Bar	Light Bar Module (USB)	Light Bar Module (USB)
	Pin Pad	Supported Verifone®P400/VX805/VX820, Ingenico iPP 350/320, LANE 3000	Supported Verifone®P400/VX805/VX820, Ingenico iPP 350/320, LANE 3000
	Cable	Converter cable for FeDP to VGA Converter cable for FeDP to HDMI	Converter cable for FeDP to VGA Converter cable for FeDP to HDMI
	Stand	POS Stand, Printer Stand, Floor Stand	POS Stand, Printer Stand, Floor Stand
	Printer Kit	Epson®TM-m30/TM-T88VI, Star TSP-654/TSP-100/mc-Print3, Xprinter XP-R330H	Epson®TM-m30/TM-T88VI, Star TSP-654/TSP-100/mc-Print3, Xprinter XP-R330H
<b>Certificate</b>	EMC & Safety	FCC Class A, CE Mark, LVD	FCC Class A, CE Mark, LVD
<b>Environment</b>	Operating Temperature	0°C ~ 40°C (32°F ~ 104°F)	0°C ~ 40°C (32°F ~ 104°F)
	Storage Temperature	-20°C ~ 60°C (-4°F ~ 140°F)	-20°C ~ 60°C (-4°F ~ 140°F)
	Humidity	20% ~ 85% RH non-condensing	20% ~ 85% RH non-condensing
<b>Dimensions</b>	W x H x D	K737N: 370 x 235 x 42.3 mm (14.6" x 9.3" x 1.7") K738N: 453 x 273 x 50.2 mm (17.8" x 10.8" x 2") K739N: 518 x 310 x 49.3 mm (20.4" x 12.2" x 1.9")	K737N: 370 x 235 x 42.3 mm (14.6" x 9.3" x 1.7") K738N: 453 x 273 x 50.2 mm (17.8" x 10.8" x 2") K739N: 518 x 310 x 49.3 mm (20.4" x 12.2" x 1.9")
<b>Weight</b>	Weight	K737N: 2.8 kg (6.2 lbs) K738N: 4.2 kg (9.3 lbs) K739N: 5.1 kg (11.2 lbs)	K737N: 2.8 kg (6.2 lbs) K738N: 4.2 kg (9.3 lbs) K739N: 5.1 kg (11.2 lbs)
<b>Mounting</b>	VESA Mount	75 x 75 mm / 100 x 100 mm	75 x 75 mm / 100 x 100 mm
<b>OS Supported</b>		Windows 10 IoT Enterprise, Linux, Android 13.0	Windows 10 IoT Enterprise, Linux, Android 13.0

\* PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE \*

## Taiwan - Headquarters

No.168, Sing-ai Rd., Neihu District,  
Taipei City 11494, Taiwan, R.O.C.  
Tel: 886-2-8791-4988  
Fax: 886-2-8791-4966  
E-mail: sales@flytech.com  
www.flytech.com

## U.S.A. - California

271 East Brokaw Road, San Jose,  
CA 95112, U.S.A.  
Tel: 1-510-257-5180  
Fax: 1-510-257-5181  
E-mail: sales.americas@flytech.com

## China - Shanghai

3F Building 39, No. 333 Qin Jiang Rd.,  
Shanghai 200233, P.R.China  
Tel: 86-21-5426-1555  
Fax: 86-21-5426-1001  
E-mail: sales@flytech.com.cn  
www.flytech.com.cn

## China - Hong Kong SAR

Rm01, 6/F, Blk A, Tonic Industrial Centre,  
26 Kai Cheung Road, Kowloon Bay,  
Kowloon, Hong Kong.  
Tel: 852-3525-5800  
Fax: 852-2751-7447  
E-mail: sales@flytech.com.hk

