

**FLYTECH**

# K669N3

19" Self-Checkout Kiosk


 Windows  Linux  Android 13



## KEY FEATURES:

- Integrated with Intel® Alder Lake-N and Meteor Lake processors
- Compatible with Windows, Linux, and Android operating systems
- 19" PCAP touchscreen for enhanced customer experience
- Comprehensive range of peripheral and accessory options
- Easy access to the motherboard box for service and maintenance
- Space-saving footprint to fit easily into any retail environment

## DIMENSIONS



## SPECIFICATIONS

		<b>G35</b>	<b>G75U</b>
<b>System</b>	<b>Motherboard</b>	<b>G35</b>	<b>G75U</b>
	Processor	Intel® Alder Lake N: N97, i3-N305	Intel® Meteor Lake Core Ultra 5 125U
	Memory	8GB DDR4	8GB DDR5
	Storage	128GB SSD (M.2)	128GB SSD (M.2)
<b>Display</b>	Size and Resolution	19" 1280 x 1024	19" 1280 x 1024
	Touch Screen	True-Flat PCAP multi-touch	True-Flat PCAP multi-touch
<b>I/O Ports</b>	USB Type-A	2 x USB3.0, 4 x USB2.0	4 x USB3.0, 2 x USB2.0
	USB Type-C	1 x USB3.0 full-functioned (DP/PD 5V/3A, 12V/3A)	1 x USB3.0 full-functioned (DP/PD 5V/3A, 12V/3A)
	FeDP	2 x Flytech proprietary miniDP (1 for the main display, 1 for the 2nd display)	2 x Flytech proprietary miniDP (1 for the main display, 1 for the 2nd display)
	Serial Port	3 x RJ48 (standard RS232) (default 0V; 5V,12V)	3 x RJ48 (standard RS232) (default 0V; 5V,12V)
	LAN	1 x RJ45	1 x RJ45
	Cash Drawer	1 x RJ11	1 x RJ11
	DC Jack	1 x 4PIN (with latch)	1 x 4PIN (with latch)
	Power Button	1	1
<b>Optional I/O Ports</b>	Powered USB	2 x Powered USB 12V, 1 x Powered USB 24V	2 x Powered USB 12V, 1 x Powered USB 24V
<b>Audio</b>	Speaker	1 x 3W	1 x 3W
<b>Power</b>	Power Supply	65W/19V (120W/19V with 2 x PUSB 12V & 1 x PUSB 24V)	120W/19V
<b>Communication</b>	WLAN+BT	802.11 series + BT5.0 (Option)	802.11 series + BT5.0 (Option)
<b>Peripherals (option)</b>	RFID	RFID Reader (USB)	RFID Reader (USB)
	MSR	3-Track MSR (USB)	3-Track MSR (USB)
	iButton	iButton (USB)	iButton (USB)
	Camera	5MP Camera (on main display) / 2MP Camera (on top pole)	5MP Camera (on main display) / 2MP Camera (on top pole)
	Light Bar	Light Bar Module	Light Bar Module
	2nd Display	11.6" 2nd display	11.6" 2nd display
	Scanner	Supported Honeywell 7990G, Datalogic M3450VSi, SuperLead 72CJ/7801	Supported Honeywell 7990G, Datalogic M3450VSi, SuperLead 72CJ/7801
	Printer	Supported Epson® TM-M30III, TM-T88VI, TM-T88VII, HPRT TP808	Supported Epson® TM-M30III, TM-T88VI, TM-T88VII, HPRT TP808
	Payment Device	Supported Verifone P400, Ingenico LANE 3000/3600 (payment bracket only)	Supported Verifone P400, Ingenico LANE 3000/3600 (payment bracket only)
	Top Pole	Top Pole Module	Top Pole Module
Mounting Kit	Wall-mount kit, Counter mount kit, Floor stand kit	Wall-mount kit, Counter mount kit, Floor stand kit	
<b>Certificate</b>	Certificate	FCC Class A, CE Mark Class A, LVD	FCC Class A, CE Mark Class A, LVD
<b>Environment</b>	Operating Temperature	0°C ~ 35°C (32°F ~ 95°F)	0°C ~ 35°C (32°F ~ 95°F)
	Storage Temperature	-20°C ~ 60°C (-4°F ~ 140°F)	-20°C ~ 60°C (-4°F ~ 140°F)
	Humidity	20% ~ 85% RH non-condensing	20% ~ 85% RH non-condensing
<b>Dimensions</b>	W x H x D	435 x 581 x 306 mm (17.1" x 22.8" x 12")	435 x 581 x 306 mm (17.1" x 22.8" x 12")
<b>Weight</b>	Weight (w/o Accessory)	13kg (28.66 lbs)	13kg (28.66 lbs)
<b>OS Supported</b>		Windows 10 IoT Enterprise, Linux, Android 13.0	Windows 10 IoT Enterprise, Linux, Android 13.0

※ PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE ※

## Taiwan - Headquarters

No.168, Sing-ai Rd., Neihu District,  
 Taipei City 11494, Taiwan, R.O.C.  
 886-2-8791-4988  
 886-2-8791-4966  
 sales@flytech.com  
 www.flytech.com

## U.S.A. - California

271 East Brokaw Road, San Jose,  
 CA 95112, U.S.A.  
 1-510-257-5180  
 1-510-257-5181  
 sales.americas@flytech.com

## China - Shanghai

3F Building 39, No. 333 Qin Jiang Rd.,  
 Shanghai 200233, P.R.China  
 86-21-5426-1555  
 86-21-5426-1001  
 sales@flytech.com.cn  
 www.flytech.com.cn

## China - Hong Kong SAR

Rm01, 6/F, Blk A, Tonic Industrial Centre,  
 26 Kai Cheung Road, Kowloon Bay,  
 Kowloon, Hong Kong.  
 852-3525-5800  
 852-2751-7447  
 sales@flytech.com.hk

