

**FLYTECH**

# KPC2

## Compact Digital Signage Player

Flytech's KPC2 is a compact digital signage player powered by the MediaTek G700 processor with GMS certification and the Intel® Elkhart Lake processor, delivering robust performance. Expandable storage options, including a microSD card slot, provide versatile application possibilities. Ideal for KDS controllers, digital signage, kiosks, and thin clients, KPC2 provides a seamless and engaging experience.


Windows Linux Android 13



### Key Features:

- Integrated with the MediaTek G700 and Intel® Elkhart Lake processors
- Compact perfection in a palm-sized form factor
- Connect up to 3 displays using HDMI and USB-C
- Expandable storage via a microSD card slot
- Expansion M.2 slot for the WLAN card and flexible antenna installation
- Built-in universal VESA mounts (75mm and 100mm) for limitless placement possibilities

## DIMENSIONS



## SPECIFICATIONS

	Motherboard	G18	F38
<b>System</b>	Processor	MediaTek G700 (MT8390)	Intel® Elkhart Lake J6412
	Memory	4GB LPDDR4	8GB DDR4
	Storage	64GB eMMC	128GB eMMC
<b>Expansion</b>	microSD Card Slot	1 <i>(** For optimal performance, please use microSD UHS-I U1 or Class 10)</i>	1 <i>(** For optimal performance, please use microSD UHS-I U1 or Class 10)</i>
<b>I/O Ports</b>	USB Type-A	3 x USB2.0, 1 x USB3.0	1 x USB2.0, 3 x USB3.0
	USB Type-C	1 x USB2.0 (data only)	1 x USB3.0 full functioned (DP / PD 5V/3A, 12V/1.25A)
	Serial Port	1 x DB9 (Powered RS232) (default: 0V)	1 x DB9 (Powered RS232) (default: 0V; 5V, 12V)
	LAN	1 x RJ45	1 x RJ45
	HDMI	2	2
	DC Jack	1 x 2pin	1 x 2pin
<b>Audio</b>	Mic-in/Line-out	1	1
<b>Power</b>	Power Adapter	36W / 12V	36W / 12V
<b>Communication</b>	WLAN + BT	WiFi 6, BT5.2	Wi-Fi 6, BT5.2 (Option)
<b>Certificate</b>	EMC & Safety	FCC Class A, CE Mark, LVD	FCC Class A, CE Mark, LVD
<b>Environment</b>	Operating Temperature	0°C ~ 35°C (32°F ~ 95°F)	0°C ~ 35°C (32°F ~ 95°F)
	Storage Temperature	-20°C ~ 60°C (-4°F ~ 140°F)	-20°C ~ 60°C (-4°F ~ 140°F)
	Humidity	20% ~ 85% RH non-condensing	20% ~ 85% RH non-condensing
<b>Dimensions</b>	W x H x D	120 x 120 x 23 mm (4.7" x 4.7" x 0.9")	120 x 120 x 23 mm (4.7" x 4.7" x 0.9")
<b>Mounting</b>	VESA Mount	75 x 75, 100 x 100	75 x 75, 100 x 100
<b>OS Supported</b>		Android 13.0 (GMS)	Windows 10 IoT Enterprise, Linux, Android 13.0

※ PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE ※

### Taiwan - Headquarters

No.168, Sing-ai Rd., Neihu District,  
Taipei City 11494, Taiwan, R.O.C.  
Tel: 886-2-8791-4988  
Fax: 886-2-8791-4966  
E-mail: sales@flytech.com.tw  
www.flytech.com

### U.S.A. - California

271 East Brokaw Road, San Jose,  
CA 95112, U.S.A.  
Tel: 1-510-257-5180  
Fax: 1-510-257-5181  
E-mail: sales@flytech.com

### China - Shanghai

3F Building 39, No. 333 Qin Jiang Rd.,  
Shanghai 200233, P.R.China  
Tel: 86-21-5426-1555  
Fax: 86-21-5426-1001  
E-mail: sales@flytech.com.cn  
www.flytech.com.cn

### China - Hong Kong SAR

Rm01, 6/F, Blk A, Tonic Industrial Centre,  
26 Kai Cheung Road, Kowloon Bay,  
Kowloon, Hong Kong.  
Tel: 852-3525-5800  
Fax: 852-2751-7447  
E-mail: sales@flytech.com.hk

