

# POS657

Robust 15.6" POS Solution





# **Key Features:**

- Featured the Intel® Alder Lake processors
- · Removable motherboard box for better serviceability
- Expandable DDR4 memory
- Tailored connectivity with the scalable I/O interface
- Optimized cable management with power adapter hidden neatly in the stand
- Featured with 12V and 24V powered USB ports to accommodate various devices

## **Dimensions**





# **Specifications**

•		
	Motherboard	G69S
	Processor	Intel® Alder Lake G6900TE / i3-12100TE / i5-12500TE
_	Memory	8GB DDR4 (max. up to 16GB with 2 x DDR4)
System	Storage	256GB SSD M.2
	Graphic Engine	Intel® UHD Graphics 710 (G6900TE)
		Intel® UHD Graphics 730 (i3-12100TE)
		Intel® UHD Graphics 770 (i5-12500TE)
Display	Size and Resolution Touch Screen	15.6" 1920 x 1080 True-Flat PCAP multi-touch
	USB Type-A	4 x USB3.0
	озв туре-А	2 x USB2.0
	USB Type-C	1 x USB3.0 full-functioned (DisplayPort/Power Delivery 5V/3A, 12V/3A)
	FeDP	1 x Flytech proprietary miniDP (for 2nd display)
	DisplayPort	1
	Serial Port	2 x DB9 (Powered RS232) (default: 0V; COM1/COM2: 0V, 5V, 12V)
I/O Ports	LAN	2 x RJ45
	Cash Drawer	1 x RJ11
	Powered USB	1 x Powered USB 12V
	DO look	1 x Powered USB 24V
	DC Jack Audio Jack	1 x 4PIN (with latch) 1 x Line-out
	Addio Jack	1 x Mic-in
Indicator	Power Button	1
	Power LED	1
Power	Power Adapter	180W / 19V
Communication	WLAN + BT	
Communication	WLAIN + BT	802.11 series + BT5.2 (Option)
Peripheral (option)	MSR	3-Track MSR (USB)
	Fingerprint	Fingerprint Reader (USB)
	Customer Display	LCM Display 2 x 20 characters (USB)
	Customer Display  2nd Display	11.6" 2nd Display (with touch)
Certificate		11.6" 2nd Display (with touch)
Certificate	2nd Display	11.6" 2nd Display (with touch) 11.6" 2nd Display (without touch)
Certificate  Environment	2nd Display  EMC & Safety	11.6" 2nd Display (with touch) 11.6" 2nd Display (without touch) FCC Class A, CE Mark, LVD
	2nd Display  EMC & Safety  Operating Temperature	11.6" 2nd Display (with touch) 11.6" 2nd Display (without touch)  FCC Class A, CE Mark, LVD  0°C ~ 35°C (32°F ~ 95°F)
	2nd Display  EMC & Safety  Operating Temperature Storage Temperature	11.6" 2nd Display (with touch) 11.6" 2nd Display (without touch)  FCC Class A, CE Mark, LVD  0°C ~ 35°C (32°F ~ 95°F) -20°C ~ 60°C (-4°F ~ 140°F)
Environment	2nd Display  EMC & Safety  Operating Temperature Storage Temperature Humidity	11.6" 2nd Display (with touch) 11.6" 2nd Display (without touch)  FCC Class A, CE Mark, LVD  0°C ~ 35°C (32°F ~ 95°F)  -20°C ~ 60°C (-4°F ~ 140°F)  20% ~ 85% RH non-condensing

\* PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE \*

## Taiwan - Headquarters

- No.168, Sing-ai Rd., Neihu District, H 105-10s, 3ing-ai-Rd., Neihu District,
  Taipei City 11494, Taiwan, R.O.C.

  886-2-8791-4988

  886-2-8791-4966

### U.S.A. - California

- ( 271 East Brokaw Road, San Jose,
- CA 95112, U.S.A.

  1-510-257-5180

  1-510-257-5181

  sales.americas@flytech.com

### China - Shanghai

- ( 3F Building 39, No. 333 Qin Jiang Rd.,
- **&** 86-21-5426-1555
- **a** 86-21-5426-1001

### China - Hong Kong SAR

- Rm01, 6/F, Blk A, Tonic Industrial Centre, 26 Kai Cheung Road, Kowloon Bay,
- 852-3525-5800 **(=)** 852-2751-7447
- sales@flytech.com.hk

